


Technical Data Sheet

Landmark™ TL Ultimate Shingles (Formerly Landmark TL)



PRODUCT INFORMATION:

The Landmark TL ULTIMATE shingles are constructed using three laminated layers of the industry's most durable materials, providing a dramatically thick roofing product styled with the classic appeal of wood shakes. The overall dimensions of this shingle are 13 1/4" x 40". It is designed to resist blow off in high wind conditions up to 110-mph.



Landmark TL ULTIMATE AR (algae resistant) shingles are algae resistant and thus protect against staining or discoloration caused by algae. AR shingles are not available in California.

Colors: Aged Bark, Birchwood, Burnt Sienna, Chestnut, Cobblestone Gray, Country Gray, Cumberland, Moiré Black, Mojave Tan, Mountain Timber, Old Overton, Platinum, Resawn Shake, Shenandoah, Sunrise Cedar and Weathered Wood. Colors may vary by region.

Limitations: It is recommended to apply these shingles at slopes of 4" per foot and greater in order to achieve optimum appearance. Low slope applications (2" up to 4" per foot) require CertainTeed's WinterGuard™ Waterproofing Shingle Underlayment, or its equivalent meeting ASTM D1970, to be applied to the entire deck surface, according to application instructions provided with the product and on the shingle package. In areas where icing along the eaves can cause the back-up of water (all slopes), apply WinterGuard, or its equivalent, according to application instructions provided with the product and on the shingle package.

Product Composition: Landmark TL ULTIMATE shingles are composed of a fiber glass mat base. Ceramic-coated mineral granules are tightly embedded in carefully refined, water-resistant asphalt. Three pieces of the shingle are firmly laminated together in a special tough asphaltic cement. All Landmark TL ULTIMATE shingles have self-sealing adhesive strips.

Applicable Standards:

ASTM D 3018, Type 1
ASTM D 3462
ASTM E 108 Class A Fire Resistance
ASTM D 3161-03b, Class "F" Wind Resistance (110-mph)
ASTM D 3161-99a, 110-mph Wind Resistance
ASTM D 7158 Class "H" Wind Resistance
UL 790 Class A Fire Resistance
UL 997 Wind Resistance
UL 2390/ASTM D6381 Class "H" Wind Resistance

NYC-MEA-120-79-M
BOCA & SBCCI Building Codes
ICC-ES Evaluation Report ESR-1389
CSA Standard A123.5-98 (& -05)
Miami-Dade Product Control Acceptance
Florida Product Approvals # FL5444

Technical Data:

Weight/Square (approx.):	340 lbs.
Dimensions (overall):	13 1/4"x 40"
Shingles/Square:	64
Weather Exposure:	5-5/8"

INSTALLATION

Installation instructions, including diagrams, are supplied on each bundle of Landmark TL ULTIMATE shingles, or separate application sheets may be obtained from CertainTeed. Following is a general summary of the installation methods. NOTE - Refer to application instructions supplied with the shingles for further information and application procedures.

Roof Deck Requirements: Apply shingles to minimum 3/8" thick plywood, minimum 7/16" thick non-veneer (E.g. OSB), or minimum 1" thick (nominal) wood decks. The plywood or non-veneer decks must comply with the specifications of APA – The Engineered Wood Association.

Ventilation: Provisions for ventilation should meet or exceed current HUD Standards. To best insure adequate ventilation, use a combination of continuous ridge ventilation (using Ridge FilterVent or Ridge Filter ShingleVent II, manufactured by Air Vent Inc, or a comparable product with an external baffle) and balanced soffit venting.

Valleys: Open valley is recommended. Valley liner must be applied before shingles. It must be minimum 18" wide 16 oz. copper, or its equivalent, installed over 36" wide self-adhering CertainTeed's WinterGuard Waterproofing Shingle Underlayment (apply directly to deck), or applied over 36" wide mineral surfaced roll roofing. After WinterGuard has been applied, install the 16-oz. copper centered in the valley. For application of copper valley, use copper cleats or large head copper nails. Closed-Cut valley application is an acceptable alternate, provided the shingles are not damaged while being formed into place. Refer to the application instructions on the shingle packaging for further information.

Underlayment: At standard slopes (4" per foot or greater) a single layer of Roofers' Select™ High-Performance shingle underlayment (or product meeting ASTM D 4869 or ASTM D 6757) is recommended. For UL fire rating, underlayment may be required. Corrosion-resistant drip edge is recommended and should be placed over the underlayment at the rake and beneath the underlayment at the eaves.

Low Slope Underlayment: On low slopes (2" to 4" per foot), CertainTeed's WinterGuard™ Waterproofing Shingle Underlayment, or equivalent self-adhering underlayment meeting ASTM D1970, must be applied to the entire deck surface, according to application instructions provided with the product and on the shingle package. When WinterGuard is applied to the rake area, the drip edge may be installed under or over WinterGuard. At the eave, when WinterGuard does not overlap the gutter or fascia, the drip edge should be installed under WinterGuard. When WinterGuard overlaps the fascia or gutter, the drip edge or other metal must be installed over it.

Fastening: Four nails are required per shingle. Nails must be of sufficient length to penetrate into the deck 3/4" or through the thickness of the decking, whichever is less. They must be placed on the nail line marked on the shingle. Fasteners are to be located 1" and 13 1/2" in from each side of the shingles (see instructions on product wraps). Nails are to be 11 or 12 gauge, corrosion-resistant roofing nails with 3/8" heads.

On slopes greater than 21" per foot, fasten each shingle with six nails and apply four 1" diameter spots of asphalt roofing cement (ASTM D 4586) placed under each shingle according to application instructions provided on the shingle package.

Application: The recommended application method is the 'Five-Course Diagonal Method (Metric)' found on each bundle of shingles. In this method, shingle course offsets are 5-5/8" and 11-1/4". Instructions also may be obtained from CertainTeed. These shingles may be used for new construction or for reroofing over shingles of 5-5/8" exposure.

Flashing: Use corrosion-resistant metal flashing.

Hips and Ridges: Use CertainTeed's Shadow Ridge™, ContourRidge™, or ElevationRidge™ accessory roofing shingles of a like color for capping hips and ridges.

MAINTENANCE

Landmark TL ULTIMATE shingles do not require maintenance when installed according to manufacturer's application instructions. However, to protect the investment, any roof should be routinely inspected at least once a year. Older roofs should be looked at more frequently.

WARRANTY

Landmark TL ULTIMATE shingles carry a lifetime limited, transferable warranty to the consumer against manufacturing defects. In addition, all Landmark TL ULTIMATE shingles carry 10-year SureStart™ Protection. For specific warranty details and limitations, refer to the warranty itself (available from the local supplier, roofing contractor or on-line at www.certainteed.com).

FOR MORE INFORMATION

Sales Support Group: 800-233-8990

Web site: www.certainteed.com

See us in Sweets and ARCAT printed and electronic publications

CertainTeed Corporation
Roofing Products Group
P.O. Box 860
Valley Forge, PA 19482

© Copyright CertainTeed Corporation, 2006.
All rights reserved. Updated: 10/2006

CertainTeed 

Quality made certain. Satisfaction guaranteed.™